


PNP Transistors

2KA2006

■ Features

- Collector Current: $I_C = -0.8A$

■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter	Symbol	Rating	Unit
Collector-Base Voltage	V_{CBO}	-40	V
Collector-Emitter Voltage	V_{CEO}	-25	V
Emitter-Base Voltage	V_{EBO}	-6	V
Collector Current -Continuous	I_C	-0.8	A
Collector Dissipation	P_c	0.3	W
Junction Temperature	T_j	150	C
Storage Temperature	T_{stg}	-55 to 150	C

■ Electrical Characteristics $T_a = 25^\circ C$

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	V_{CBO}	$I_C = -100 \mu A, I_E = 0$	-40			V
Collector-emitter breakdown voltage *	V_{CEO}	$I_C = -1mA, I_B = 0$	-25			V
Emitter-base Breakdown voltage	V_{EBO}	$I_E = -100 \mu A, I_C = 0$	-6			V
Collector-base cut-off current	I_{CB0}	$V_{CB} = -35V, I_E = 0$			-0.1	μA
Collector-emitter cut-off current	I_{CEO}	$V_{CE} = -20 V, I_B = 0$			-0.1	μA
DC current gain	h_{FE}	$V_{CE} = -1 V, I_C = -1mA$	45			
		$V_{CE} = -1 V, I_C = -100 mA$	200		350	
		$V_{CE} = -1 V, I_C = -800 mA$	40			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -800 mA, I_B = -80 mA$			-0.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C = -800 mA, I_B = -80 mA$			-1.2	V
Transition frequency	f_T	$V_{CE} = -6 V, I_C = -20 mA, f = 30 MHz$	150			MHz

* Pulse Test : pulse width $\leq 300 \mu s$, duty cycle $\leq 2\%$.

■ Marking

Marking	2B
---------	----

PNP Transistors

2KA2006

■ Typical Characteristics




Figure 1. Static Characteristic





Figure 2. DC current Gain



**Figure 3. Base-Emitter Saturation Voltage
Collector-Emitter Saturation Voltage**




Figure 4. Base-Emitter On Voltage




Figure 5. Collector Output Capacitance




Figure 6. Current Gain Bandwidth Product